



INVISIBLE GROUT SEAL

ORIGINAL GROUT COLOUR GUARANTEED • MATT FINISH • EXTREMELY STAIN RESISTANT • ONE COAT APPLICATION

Invisible Grout Seal is specifically formulated to maintain a grout's original matt colour whilst creating a stain resistant and water proof finish. **Invisible Grout Seal** is recommended for all grout joint installations.

SUITABLE GROUTS

All

SUITABLE SUBSTRATES

All

INTERIOR/EXTERIOR

Walls

Floors

COLOUR

Clear

PRECAUTIONS

Invisible Grout Seal is unsuitable for:

- sealing moisture sensitive green marble joints
- wet grouts; surfaces to be treated must be thoroughly dry

SPECIAL CARE REQUIRED

Test a small area prior to sealing the whole tile joint installation. Residues must be rinsed off tiles & metal fittings with water. Spills on fabrics must be rinsed off immediately with water to avoid staining and permanent damage.

TILE JOINT PREPARATION & WATER CONTENT

Tile joints must be thoroughly cleaned of all dust and any other contaminants. Use **Invisible Grout Seal** on dry grout joints only.

New Grout Installations: Seal 7 days after damp curing.

Old Grout Installations: Seal 24 hours after cleaning.

APPLICATION & TOOLS

Invisible Grout Seal should be applied undiluted using a brush. Working within small areas at a time, completely wet the joint with **Invisible Grout Seal**. Avoid using excess sealer and immediately wipe up any residues with a clean & damp cloth.

COVERAGE

Coverage is approximate only and will vary according to the porosity of the grout and the dimensions of the tile joint. As a guide, 1 litre of **Invisible Grout Seal** will cover approximately 50 square metres of regular grout joints with a width of 4mm.

CURE TIME

Invisible Grout Seal cures in approximately 24 hours at 23°C and 50% relative humidity. Temperatures during installation below 10°C will significantly increase the cure time.

CLEAN UP

Wet **Invisible Grout Seal** can be cleaned off any surface or material with water.

EXPECTED WEAR

Invisible Grout Seal has an approximate wear life of 3 to 5 years on exterior installations and at least 5 years on interior installations. **Invisible Grout Seal** may be adversely affected by repeated exposure to concentrated acid or alkali based cleaners.

INVISIBLE GROUT SEAL

**FREE TECHNICAL ADVICE
& MATERIAL SAFETY DATA SHEETS**
Email: info@morganadhesives.com.au
Helpline: (08) 9441 6677 Response within 24 hrs

ORIGINAL GROUT COLOUR GUARANTEED • MATT FINISH • EXTREMELY STAIN RESISTANT • ONE COAT APPLICATION

SHELF LIFE

Twelve months if stored in a dry & elevated position in the original factory sealed packaging.

PACKAGING

Invisible Grout Seal is available in 1L containers.

SPECIFICATION CLAUSE

The wall & floor grout sealer shall be Morgan **Invisible Grout Seal** - a high performance grout sealer.

MORGAN QUALITY POLICY STATEMENT

Invisible Grout Seal is manufactured and distributed to a quality system based on ISO 9001:2000. **Invisible Grout Seal** is guaranteed for 3 years when applied in conjunction with written technical information supplied by **Morgan Ceramic Tile Adhesives**.

USER NOTE Although the technical details and recommendations contained in this brochure correspond to the best of our knowledge and experience, all of the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in any case the user is fully responsible for all consequences deriving from the use of the product.



24 Hanwell Way, Bassendean WA 6054
Ph: 08 9279 8911 • Fx: 08 6278 1152

www.morganadhesives.com.au