



STONE SEAL

CLEAR & MATT

**ORIGINAL STONE COLOUR GUARANTEED • MATT FINISH •
STAIN & MOULD RESISTANT • PRE-SEAL SEALER**

Stone Seal is specifically formulated to maintain a stones original colour whilst creating a stain resistant and mould proof finish. **Stone Seal** is recommended for porous stone installations as a pre-seal to solvent based sealers so as to maintain a stones natural & subtle colour.

SUITABLE TILES

Natural Stone	Bicottura
Marble	Limestone
Concrete	Paving Bricks

SUITABLE SUBSTRATES

All

INTERIOR/EXTERIOR COLOUR

Walls	Clear
Floors	

PRECAUTIONS

Stone Seal is unsuitable for:

- sealing moisture sensitive green marble
- non-porous tiles

SPECIAL CARE REQUIRED

Test a small area prior to sealing the whole tile installation. Residues must be rinsed off tiles & surrounding fittings with water. Spills on fabrics must be rinsed off immediately with water to avoid staining and permanent damage.

TILE FLOOR PREPARATION

Tile and tile joints must be thoroughly cleaned of all dust and any other contaminants. Use **Stone Seal** on thoroughly dry tiles only.

New Tile Installations: Seal 7 days after curing.

Old Tile Installations: Seal 24 hours after cleaning.

APPLICATION & TOOLS

Stone Seal should be applied undiluted using a brush. Semi-porous tiles will need a cloth application of the sealer. A thin application, free of bubbles, is recommended for best results. Working within small areas at a time, completely wet the installation with **Stone Seal**. Avoid using excess sealer and wipe up any residues after 1 or 2 minutes with a clean cloth. Avoid overlapping the sealer during application. For a more durable finish, apply a second coat of **Stone Seal** after 24 hours.

COVERAGE

Coverage is approximate only and will vary according to the porosity of the tiles. As a guide, 1 litre of **Stone Seal** will cover approximately 8 square metres of floor.

CURE TIME

Stone Seal cures in approximately 24 hours at 23°C and 50% relative humidity. Temperatures during installation below 10°C will significantly increase the cure time. Sealed floors are ready for light traffic after a couple of hours.

CLEAN UP

Wet **Stone Seal** can be cleaned off any surface or material with water.

EXPECTED WEAR

Stone Seal has an approximate wear life of 3 to 5 years on exterior installations and at least 5 years on interior installations.

STONE SEAL

CLEAR & MATT

**FREE TECHNICAL ADVICE
& MATERIAL SAFETY DATA SHEETS**
Email: info@morganadhesives.com.au
Helpline: (08) 9441 6677 Response within 24 hrs

ORIGINAL STONE COLOUR GUARANTEED • MATT FINISH • STAIN & MOULD RESISTANT • PRE-SEAL SEALER

SHELF LIFE

Twelve months if stored in a dry & elevated position in the original factory sealed packaging.

PACKAGING

Stone Seal is available in 20L, 10L, 5L & 1L containers.

SPECIFICATION CLAUSE

The wall & floor sealer shall be **Morgan Stone Seal** - a high performance tile sealer.

MORGAN QUALITY POLICY STATEMENT

Stone Seal is manufactured and distributed to a quality system based on ISO 9001:2000. **Stone Seal** is guaranteed for 3 years when applied in conjunction with written technical information supplied by **Morgan Ceramic Tile Adhesives**.

USER NOTE Although the technical details and recommendations contained in this brochure correspond to the best of our knowledge and experience, all of the above information must, in every case, be taken as merely indicative and subject to confirmation after long term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in any case the user is fully responsible for all consequences deriving from the use of the product.



24 Hanwell Way, Bassendean WA 6054
Ph: 08 9279 8911 • Fx: 08 6278 1152

www.morganadhesives.com.au